



SHREDDERS-AND-CHIPPERS

VERSION | R225BHHP13



BASIC EQUIPMENT

- ROTOR | Blades + Hammers
- Sharpenable blades (hardened steel)
- Mobile reversible hammers (hardened steel)
- Hydraulic feeding roller with adjustable speed and rotation direction
- Rotary ejection pipe with adjustable discharge distance
- Large and handy hopper
- Lubrication system for bearings
- Belt transmission with hydrodynamic joint
- Trailer with 4 pneumatic wheels + drawbar
- HONDA GX390

ACCESSORIES

- Ejection pipe extension (400 mm)
- Refining screen kit (Fixed removable refining screen)

CUTTING SYSTEM

Blades (hardened steel)	N°	2
Hammers (hardened steel)	N°	8
Counter-blade	N°	1

FEATURES

Hourly capacity	m ³ /h*	6 - 7
Throat opening	mm	160 x 90
To shred - Ø max.*	mm	90

MOTIVE POWER

Power	hp/kW	13 / 9,6
Power source		Petrol
Engine/motor		HONDA GX390
Fuel consumption	liters/h	2,8

SPECIFICATIONS

Length	mm	2385
Width	mm	930
Height	mm	1820
Discharge height	mm	1820
Introduction height	mm	1010
Hopper size	mm	700 x 660
Weight: NET	kg	325

* Input material - Data depending on the kind of material and working conditions.

**TERMS**

Product origin	Made in Italy
Warranty	The warranty is the one established by law and it's valid just upon submission of the machine's sales document.
Delivery - Original spare parts	Usually available, 45 days max. (from order date)
Identification - SCIP number (link)	https://echa.europa.eu/it/scip-database

The products are subject to technical evolution and this website may not be fully updated.
The data in the tables, the photos and pictures have to be considered informative and not binding.