




SHREDDERS-AND-CHIPPERS

VERSION | R260TPTN



BASIC EQUIPMENT

- ROTOR | Blades + Hammers
- Sharpenable blades (hardened steel)
- Mobile reversible hammers (hardened steel)
- Fixed removable refining screen
- Hydraulic feeding roller with adjustable speed and rotation direction
- Feeding conveyor belt in steel with adjustable speed and rotation direction
- Rotary ejection pipe with adjustable discharge distance
- Large and handy hopper
- Lubrication system for bearings
- OBS - On Board System (Multifunctional control system with Nostress)
- Belt transmission with gearbox
- Three-point linkage for tractor - Category 1/2

ACCESSORIES

- Ejection pipe extension (400 mm)
- CE marked cardan shaft with freewheel

CUTTING SYSTEM

Blades (hardened steel)	N°	2
Hammers (hardened steel)	N°	20
Counter-blade	N°	1

FEATURES

Hourly capacity	m ³ /h*	10 - 14
Throat opening	mm	230 x 130
To shred - Ø max.*	mm	130

MOTIVE POWER

Power	hp/kW	≥ 35 / 25,7
Power source		Three-point linkage for tractor / TRANSVERSE MACHINE
Engine/motor		Tractor
Fuel consumption	liters/h	/

SPECIFICATIONS

Length	mm	1650
Width	mm	2520
Height	mm	2190
Discharge height	mm	2190
Introduction height	mm	800
Hopper size	mm	1180 x 830
Weight: NET	kg	660

* Input material - Data depending on the kind of material and working conditions.

**TERMS**

Product origin	Made in Italy
Warranty	The warranty is the one established by law and it's valid just upon submission of the machine's sales document.
Delivery - Original spare parts	Usually available, 45 days max. (from order date)
Identification - SCIP number (link)	https://echa.europa.eu/it/scip-database

The products are subject to technical evolution and this website may not be fully updated.
The data in the tables, the photos and pictures have to be considered informative and not binding.