



SHREDDERS-AND-CHIPPERS

VERSION | R335TTN-M



BASIC EQUIPMENT

- ROTOR | Hammers
- Mobile reversible hammers (hardened steel)
- Fixed removable refining screen
- Hydraulic feeding roller with adjustable speed and rotation direction
- Rotary ejection pipe with adjustable discharge distance
- Large and handy hopper
- Lubrication system for bearings
- OBS - On Board System (Multifunctional control system with Nostress)
- Belt transmission with gearbox
- Homologated road trailer at reduced speed + Fixed drawbar with towing eye

ACCESSORIES

- Ejection pipe extension (400 mm)
- CE marked cardan shaft

CUTTING SYSTEM

Blades (hardened steel)	N°	/
Hammers (hardened steel)	N°	68
Counter-blade	N°	1

FEATURES

Hourly capacity	m ³ /h*	15 - 20
Throat opening	mm	390 x 160
To shred - Ø max.*	mm	160

MOTIVE POWER

Power	hp/kW	≥ 40 / 29,5
Power source		Towed by tractor
Engine/motor		Tractor
Fuel consumption	liters/h	/

SPECIFICATIONS

Length	mm	4120
Width	mm	1580
Height	mm	2320
Discharge height	mm	2320
Introduction height	mm	740
Hopper size	mm	1340 x 860
Weight: NET	kg	740

* Input material - Data depending on the kind of material and working conditions.

**TERMS**

Product origin	Made in Italy
Warranty	The warranty is the one established by law and it's valid just upon submission of the machine's sales document.
Delivery - Original spare parts	Usually available, 45 days max. (from order date)
Identification - SCIP number (link)	https://echa.europa.eu/it/scip-database

The products are subject to technical evolution and this website may not be fully updated.
The data in the tables, the photos and pictures have to be considered informative and not binding.