



## VACUUMS

## VERSION | TORNADOPTO



## BASIC EQUIPMENT

- IMPELLER | 8 paddles
- Paddles in steel
- Suction hose (rigid hose + flexible hose)
- Rotary support for flexible hose
- Folding, rotary ejection pipe with adjustable discharge distance
- Replaceable inner cover
- Twin belt transmission with gearbox
- Three-point linkage for tractor - Category 1

## ACCESSORIES

- Flexible suction hose extension (5000 mm)
- CE marked cardan shaft with freewheel

## VACUUM SYSTEM

Impeller - Ø	mm	390
Paddles (steel)	N°	8
Suction hose - Ø	mm	200

## FEATURES

Suction power	m <sup>3</sup> /minute*	170
---------------	-------------------------	-----

## MOTIVE POWER

Power	hp/kW	≥ 13 / 9,6
Power source		Three-point linkage for tractor / LONGITUDINAL MACHINE
Engine/motor		Tractor
Fuel consumption	liters/h	/

## SPECIFICATIONS

Length	mm	1360/1795
Width	mm	820
Height	mm	1780/2135
Weight: NET	kg	240
Suction hose length (rigid hose + flexible hose)	mm	1000 + 5000

\* Input material - Data depending on the kind of material and working conditions.

**TERMS**

Warranty	The warranty is the one established by law and it's valid just upon submission of the machine's sales document.
Product origin	Made in Italy
Delivery - Original spare parts	Usually available, 45 days max. (from order date)
Identification - SCIP number (link)	<a href="https://echa.europa.eu/it/scip-database">https://echa.europa.eu/it/scip-database</a>

The products are subject to technical evolution and this website may not be fully updated.  
The data in the tables, the photos and pictures have to be considered informative and not binding.