



## VACUUMS

## VERSION | TORNBH21TRG



## BASIC EQUIPMENT

- IMPELLER | 8 paddles
- Paddles in steel
- Suction hose (rigid hose + flexible hose)
- Rotary support for flexible hose
- Folding, rotary ejection pipe with adjustable discharge distance
- Replaceable inner cover
- Twin belt transmission with centrifugal clutch
- Adjustable drawbar with ball hitch coupling
- HONDA GX630
- Electric start

## ACCESSORIES

- Flexible suction hose extension (5000 mm)

## VACUUM SYSTEM

Impeller - Ø	mm	390
Paddles (steel)	N°	8
Suction hose - Ø	mm	200

## FEATURES

Suction power	m <sup>3</sup> /minute*	170
---------------	-------------------------	-----

## MOTIVE POWER

Power	hp/kW	21 / 15,5
Power source		Petrol
Engine/motor		HONDA GX630
Fuel consumption	liters/h	4,8

## SPECIFICATIONS

Length	mm	2300
Width	mm	1280
Height	mm	2000/2330
Weight: NET	kg	375
Suction hose length (rigid hose + flexible hose)	mm	1000 + 5000

\* Input material - Data depending on the kind of material and working conditions.

**TERMS**

Warranty	The warranty is the one established by law and it's valid just upon submission of the machine's sales document.
Product origin	Made in Italy
Delivery - Original spare parts	Usually available, 45 days max. (from order date)
Identification - SCIP number (link)	<a href="https://echa.europa.eu/it/scip-database">https://echa.europa.eu/it/scip-database</a>

The products are subject to technical evolution and this website may not be fully updated.  
The data in the tables, the photos and pictures have to be considered informative and not binding.